

TECHNICAL SPECIFICATION SHEET FOR ESQTEC

Marketing Information	
Code	ESQTECL-UL
Model	ESQTEC
Capacity [ft ³]	25
Capacity [lt]	732
Market/Country	National/Exportation
Dimension with packaging [in]*	L:89 P:53 A:57
Dimension without packaging [in]*	L79.52 P:46.45 A:45.27
Accessories	
User´s Guide	Yes
Wheels	N/A
Safety Recommendations	Yes
Shelves Line	
Quantity (Pieces)	Inferior grills (5)
	Exhibition grills (5)
	Display trays (1)
Materials	Wire (Available on Commercial Steel and Stainless steel)
Clamps	Adjustable
Colors	White
Doors	
Quantity (Pieces)	Glass door (1)
	Solid door (1)
Door Type	Glass door (Hinged) Solid Door (Hinged)
Door Construction	Glass, solid
Materials	glass door (crystal), solid door (high density polyurethane)
Colors	black, white
Closing method	Selfclosing/Manual
Glass Quantity in Sandwich	2
Handles	
Quantity (Pieces)	3
Materials	Steel
Color	Black
Finished	
Interior	Stainless steel
Exterior	Prepainted white sheet
Isolation mode	High density polyurethane
Electrical Characteristics	
Nominal Voltage [V]	110
Nominal Current [A]	1.6
Frecuency [Htz]	60
Method of Lighting	LED
Cooling System	
Compressor (HP)	External Unit, contact your dealer
Condenser	External Unit, contact your dealer
Evaporator	Forced Ventilation, natural convection
Expansion Method	External Unit, contact your dealer

Note: All controls reach temperature until 75°F

* L= Length, D= Depth, H= Height

REVISION: 2
DATE: 17/04/13