

## TECHNICAL SPECIFICATION SHEET FOR PTP11

Marketing Information	
Code	PTP11-ULH
Model	PTP170
Capacity [ft <sup>3</sup> ]	22.45
Capacity [lt]	635.73
Market/Country	Domestic/Exportation
Dimension with packaging [in]*	W:75 D:43.3 H:46.06
Dimension without packaging [in]*	W:67.71 D:35.03 H:40.55
Accessories	
User Guide	Yes
Safety Recommendations	Yes
Wheels	Yes
Quantity of cooking Inserts	9
Material of work table	Sanalite
Liquid Evaporating Tray	Yes
Temperature Control	Digital Temperature Control
Technical Characteristics	
Refrigerant	R134a
Evaporation Temperature [°F]	19.4
Condensation Temperature [°F]	113
Defrost Method	N/A
Optimal Temperature Range ** [°F]	Exhibition 33.8°F to 41°F
	Storage 33.8°F to 39.2°F
Shelves Line	
Quantity (Pieces)	2
Materials	Steel
Clamps	Adjustable
Colors	White
Doors	
Quantity (Pieces)	2
Door Type	Solid
Materials	Stainless steel and plastic
Colors	Stainless steel
Closing method	Manual
Handles	
Quantity (Pieces)	2
Materials	Plastic
Colors	Black
Finished	
Interior	Prepainted white sheet
Exterior	Stainless steel
Isolation mode	High density polyurethane
Electrical Characteristics	
Nominal Voltage [Volts]	120
Nominal Current [A]	8.03
Frecuency [Hz]	60
Method of Lighting	Fluorescent lamp
Cooling System	
Compressor (HP)	(1/3)
Condenser	Forced Ventilation
Evaporator	Forced Ventilation
Expansion Method	Capillary tube

Specified by NSF\*\* Note: All controls reach temperature until 75F°

\* W= Wide. D= Depth. H= Height

REVISION: 4  
DATE: 07/29/14