

# TECHNICAL SPECIFICATION SHEET

## R16L-ULH

Marketing Information	
Code/Model	R16L-ULH
Gross Capacity	16 Cu.Ft.
Storage capacity [ft <sup>3</sup> ]	12.855
Storage capacity [lt]	364
Market/Country	Domestic/International
Dimension with packaging [in]	W:35.5 D:37.5 H:88
Dimension without packaging [in]	W: 30 D: 28.34 H:78.75
Accessories	
User Guide	Yes
Safety Recommendations	Yes
Liquid Evaporating Tray	Yes
Wheels	Optional
Temperature Control	Digital Temperature Control
Technical Characteristics	
Refrigerant	R134a
Evaporation Temperature [°F]	20
Condensation Temperature [°F]	109.4
Defrost Method	n/a
Optimal Temperature Range ** [°F]	32° to 40°
Shelves Line	
Quantity (Pieces)	4
Material	Steel
Clamps	Adjustable
Color	White
Doors	
Quantity (Pieces)	1
Door Type	Swing
Door Construction	Glass
Material	Glass and plastic
Color	Black
Closing method	Self-closing
Glass Quantity in Sandwich	3
Handles	
Quantity (Pieces)	1
Material	ABS Plastic
Color	Black
Finished	
Interior	Prepainted white sheet and stainless steel
Exterior	Galvanized Sheet and prepainted white sheet
Isolation mode	High density polyurethane
Electrical Characteristics	
Nominal Voltage [V]	120
Nominal Current [A]	9,82
Frecuency [Hz]	60
Lighting Type	LED
Cooling System	
Compressor (HP)	(1/3)
Condenser	Forced Ventilation
Evaporator	Forced Ventilation
Expansion Method	Capillary

Specified by NSF\*\*

Note: All controls reach temperature until 75°F

\* w= Weigth, D= Depth, H= Height

REVISION: 5  
DATE: 08/12/2014